



Controls at the bottom

Right-hinged

BM 270 100

Anthracite full glass door

Width 60 cm

BM 270 110

Stainless steel-backed full glass door

Width 60 cm

BM 270 130

Aluminium-backed full glass door

Width 60 cm

Left-hinged

BM 271 100

Anthracite full glass door

Width 60 cm

BM 271 110

Stainless steel-backed full glass door

Width 60 cm

BM 271 130

Aluminium-backed full glass door

Width 60 cm

Controls at the top

Right-hinged

BM 274 100

Anthracite full glass door

Width 60 cm

BM 274 110

Stainless steel-backed full glass door

Width 60 cm

BM 274 130

Aluminium-backed full glass door

Width 60 cm

Left-hinged

BM 275 100

Anthracite full glass door

Width 60 cm

BM 275 110

Stainless steel-backed full glass door

Width 60 cm

BM 275 130

Aluminium-backed full glass door

Width 60 cm

Included in the price

1 combination wire rack

1 enamel baking tray



Combi-microwave oven 200 series BM 270/BM 271/BM 274/BM 275

- Combinability with other appliances of the oven 200 series in the 45 cm high niche
- Single operation and combination of microwave, grill and oven
- Sequential operation of up to 3 modes
- Interior volume 36 litres
- 15 automatic programmes

Handling

LCD function display with digital clock. Clear text display in 16 languages. Timer functions: cooking time, switch off time, short-term timer, stop watch, long-term timer.

Actual temperature display. Electronic temperature control. Rotary knob and touch key operation. Information key with use indicators.

Programmes

Microwave operation with 5 output levels: 1000, 600, 360, 180, 90 W.

Full surface grill with 3 levels of intensity, maximum output 2000 W.

Oven operation with 3 heating methods:

Hot air 40 °C and from 100 °C to 250 °C,

grilling with hot air from 100 °C to 250 °C,

grilling with circulated air from 100 °C to 250 °C.

Heating methods with microwave

output levels 600, 360, 180 and 90 W

freely combinable.

15 automatic programmes with weight

indication, customisable:

4 defrosting programmes

5 cooking programmes

6 combination programmes

Features

Innwave.

Rapid heating.

4 rack levels.

60 W halogen light on the side.

Side-opening door opens up to 180°

angle.

Safety

Triple door lock.

Child lock.

Safety shut-off.

Cooled housing with temperature

protection.

Cleaning

Stainless steel interior with ceramic

base.

Interior back wall with catalytic special

enamelling.

Planning notes

Plan the niche without back wall.

Door hinge not reversible.

The façade of the appliance extends

47 mm from the furniture cavity.

The outer edge of the door handle

extends 94 mm from the furniture cavity.

Consider the overhang, incl. the door

handle, when planning to open

drawers next to the appliance.

When planning a corner solution, pay

attention to the 90° door opening

angle.

The mains socket needs to be planned

outside of the niche.

Connection

Total connected load 3.1 kW.

Connecting cable 1.5 m without plug.

