



Controls at the bottom

Right-hinged

BS 270 101

Anthraxite full glass door
Width 60 cm

BS 270 111

Stainless steel-backed full glass door
Width 60 cm

BS 270 131

Aluminium-backed full glass door
Width 60 cm

Left-hinged

BS 271 101

Anthraxite full glass door
Width 60 cm

BS 271 111

Stainless steel-backed full glass door
Width 60 cm

BS 271 131

Aluminium-backed full glass door
Width 60 cm

Controls at the top

Right-hinged

BS 274 101

Anthraxite full glass door
Width 60 cm

BS 274 111

Stainless steel-backed full glass door
Width 60 cm

BS 274 131

Aluminium-backed full glass door
Width 60 cm

Left-hinged

BS 275 101

Anthraxite full glass door
Width 60 cm

BS 275 111

Stainless steel-backed full glass door
Width 60 cm

BS 275 131

Aluminium-backed full glass door
Width 60 cm

Included in the price

- 1 Gastronorm insert, stainless steel, GN 2/3 unperforated
- 1 Gastronorm insert, stainless steel, GN 2/3 perforated
- 1 wire rack
- 1 outlet hose (3 m long)
- 1 water inlet hose (3 m long)
- 1 plug-in core temperature probe

Installation accessories

GZ 010 011

Aqua stop extension (2 m long)
Extends the water inlet and outlet.

WF 040 020

Descaling and neutralising filter

WF 040 021

Filter cartridges

Set of three filter cartridges.

Special accessories

GN 114 130

Gastronorm insert, stainless steel,
GN 1/3
Unperforated, 40 mm deep, 1.5 L

Combi-steam oven 200 series

BS 270/BS 271/BS 274/BS 275

- Fixed connection for water inlet and outlet
- Hot air circulation 30 °C to 230 °C at variable humidity levels of 0%, 30%, 60%, 80% or 100%, freely combinable
- Steaming without pressure
- Full surface grill behind glass ceramic for easy cleaning, combinable with circulated air up to 230 °C and steam
- Core temperature probe, removable
- Net volume 44 litres
- Energy efficiency class A

Cooking methods

Combi-steaming, steam baking, juice extraction, grilling, grilling with circulated air, grilling with steam, low temperature steaming, low temperature cooking, regeneration, thawing, dough fermentation, misting.

Handling

LCD function display with digital clock. Timer functions: cooking time, switch off time, short-term timer, stop watch, long-term timer. Settings menu with clear text display. Actual temperature display. Electronic temperature control. Save up to 6 memory recipes (incl. core temperature probe). Rotary knob and touch key operation.

Features

Full surface grill 2000 W behind glass ceramic. Core temperature probe with automatic shut off. Automatic boiling point detection. Capacity display for filter cartridge (if connected to WF 040 020 Brita descaling system). 60 W halogen light on the side. Hygienic stainless steel interior. 4 rack levels. Side-opening door opens up to 180° angle.

Safety

Steam removal. Child lock. Safety lock. Cooled housing with temperature protection.

Cleaning

Cleaning programme. Drying programme. Grease filter in front of hot air fan.

Planning notes

Door hinge not reversible. At no point may the outlet hose be positioned higher than the bottom edge of the appliance. The outlet hose must also be at least 100 mm lower than the appliance outlet (see drawing "drain connection"). The outlet hose must not be longer than a maximum of 5 m. The water connection (1) for the inlet hose must always be accessible and not located directly behind the appliance. The connection of the outlet hose to the siphon (2) must not be directly behind the appliance and should be accessible. The descaling system WF 040 020 (3) must be installed when connecting the appliance if the water hardness exceeds 7° dH.

GN 114 230

Gastronorm insert, stainless steel, GN 2/3

Unperforated, 40 mm deep, 3 L

GN 124 130

Gastronorm insert, stainless steel, GN 1/3

Perforated, 40 mm deep, 1.5 L

GN 124 230

Gastronorm insert, stainless steel, GN 2/3

Perforated, 40 mm deep, 3 L

GN 340 230

Gastronorm roaster in cast aluminium

GN 2/3, height 165 mm, non-stick

GN 410 130

Gastronorm lid, stainless steel, GN 1/3

GN 410 230

Gastronorm lid, stainless steel, GN 2/3

GR 220 046

Wire rack, chromium-plated

Without opening, with feet.

The façade of the appliance extends 47 mm from the furniture cavity. The outer edge of the door handle extends 94 mm from the furniture cavity. Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 90° door opening angle. To achieve the 550 mm installation depth, the water hoses and connecting cable needs to follow the slanted edge on the lower left hand corner of the housing and then be led down and up, respectively. The mains socket needs to be planned outside of the niche.

Please read the installation details regarding air ducting on page 18/19.

Connection

Energy efficiency class A. Total connected load 2.9 kW. Only cold water connection. Supply hose 3.0 m with 3/4" connection. Outlet hose (ø 25 mm) 3.0 m (HT-Hose). Plan a connecting cable.

